



Bär VanLift FreeAccess – the revolutionary Cargolift

Bär Cargolift –
more than just a taillift

Up until now you had to decide: between free access to the cargo space or safe loading and unloading with a taillift. These times now belong to the past. FreeAccess is the magic word for your Crafter. With FreeAccess you kill two birds with one stone. With the platform folded, you have completely free access to the cargo space, unfolded it's the perfect partner for loading pallets and trolleys.

With this technology, Bär once again sets new standards of functionality, ease of use, stability and lightness. Of course you can decide to take the standard version too. As you wish. The payload loss is the same for both: Only 179 kilos.

VanLift FreeAccess

BC 502 A2V

BC 602 A2V

BC 603 A2V

VanLift Standard

BC 502 S2V

BC 602 S2V

BC 603 S2V

VW Crafter

BÄR
Cargolift®

Bär VanLift FreeAccess – The Genius

The easiest way to deliver



Free, safe access without moving the lift.



Open hydraulically and unfold by hand.



The two-part VanBridge connects the vehicle floor and the platform. Platform safety with TracGrip and SideGrip.



Enough room for euro pallets and lift trucks. Extremely low approach angle (6.2°). Please keep in mind pallet weight.



Standard: The trolley stop for 4 laundry trolleys or 1 foodstuffs trolley.



Intuitive: Radio-control unit with safety timer.



Emergency control unit.



Bär VanLift Standard.

Basic specifications: Crafter

Wheelbase (mm)	MWL/t	VanLift	Max loading (kg)
3.250 Compact	3,0/3,5	–	–
3.665 Standard	3,0/3,5	BC 602A2V BC 602S2V	600
3.665 Standard	5,0	BC 603A2V BC 603S2V	600
4.325 Long	3,5/5,0	BC 502A2V BC 502S2V	500
4.325 Extralong	4,6/5,0	BC 502A2V BC 502S2V	500

High roof needed.

Fitment impossible when vehicle is equipped with air suspension!

Fitment without changing body

Required special accessories

PR-No.	Description	recom- mended	re- quired	N/A
8FD	Additional battery		●	
UF3	Connector strip		●	
5BD	Wooden floor		●	
GC4	Increaded roll stabilisation Chassis package C		●	
5V4	Double-wing rear doors 270 degrees	●		
1B1	Spare wheel holder			●
OP6 OP7	"Exhaust"			●
8M1	Washer/wiper system			●
QT4 QT7 QT9	"Step"			●
7X2	Parktronic System front/rear			●
8HG	Generator*			●
1D7	Electronic installations Ball coupling **			●
*	Only required for short distances.			
**	Retro-fitting complex and very expensive. Standard ball coupling not possible.			

Platform dimensions

VanLift	Height (mm)	Width (mm)
FreeAccess, all types	1810	1330
Standard, all types	1810	1380

Platform finish

White aluminium RAL 9006 semi gloss (A2V)
Aluminium nature (S2V)

Special accessories

- Detachable ball coupling (complete)
Towing load: as per original Crafter
Permitted drawbar load: 120 kg, weight: 28 kg
PR-No. 1D7 (socket from VW) required!
- Emergency control unit

Industrial property rights applied

Article no. 70.133458
Technical modifications subject to modification. 06/09

