



Bär VanLift FreeAccess – the revolutionary Cargolift

Bär Cargolift –
more than just a taillift

Up until now you had to decide: between free access to the cargo space or safe loading and unloading with a taillift. These times now belong to the past. FreeAccess is the magic word for your Interstar. With FreeAccess you kill two birds with one stone. With the platform folded, you have completely free access to the cargo space, unfolded it's the perfect partner for loading pallets and trolleys.

With this technology, Bär once again sets new standards of functionality, ease of use, stability and lightness. Of course you can decide to take the standard version too. As you wish. The payload loss is the same for both: Only 178 kilos.

VanLift FreeAccess
BC 607A2V

VanLift Standard
BC 607S2V

Nissan Interstar

BÄR
Cargolift®

Bär VanLift FreeAccess – The Genius

The easy way to deliver



Free, safe access without moving the lift.



Open hydraulically and unfold by hand.



The two-part VanBridge connects the vehicle floor and the platform. Platform safety with TracGrip and SideGrip.



Enough room for euro pallets and lift trucks. Extremely low approach angle (6.2°). Please keep in mind pallet weight.



Standard: The trolley stop for 4 laundry trolleys or 1 foodstuffs trolley.



Intuitive: Radio-control unit with safety timer.



Emergency control unit.



Bär VanLift Standard.

Basic specifications Nissan Interstar

Wheelbase (mm)	MWL/t	VanLift	Max loading (kg)
all	all	BC 607A2V BC 607S2V	600
At least roof version H2 needed			
With air suspension no application possible!			
Fitting installation does not interfere with original chassis			

Required special accessories

Code	Short text	re-com.	re-quir.	N/A
	Wooden floor		●	
	Double-wing rear doors 270 degrees or	●		
	Double-wing rear doors 270 degrees with window	●		
	Parktronic			●
	Socket with electric connection only required for ball coupling system (Standard ball coupling not possible)			

Platform dimensions

VanLift	Height (mm)	Width (mm)
FreeAccess	1810	1330
Standard	1810	1380

Platform finish

White aluminium RAL 9006 semi gloss (A2V)
Aluminium nature (S2V)

Special accessories

- Detachable ball coupling (complete)
Trailer loading: according to original
Permitted drawbar load:
according to original
weight: 28 kg
- Emergency control unit

Industrial property rights apply

Article no. 70135350
Technical modifications subject to modification. 06/09



Gerd Bär GmbH · Industriegebiet Böllinger Höfe · Pfaffenstraße 7 · D 74078 Heilbronn

Phone +49 7131 2877-992 · Fax +49 7131 2877-912 · vk@baer-cargolift.de · www.baer-cargolift.com